


Precision Gate Rollers Incorporated


Product Specification Sheet

All rollers manufactured by Precision Gate Rollers Inc. use maintenance free permanently lubricated sealed ball bearings. All chassis are hot dipped galvanized to prevent rusting. Rollers are held on their shafts by a nylon imbedded lock nut.




FS-8000-HD graphite impregnated nylon cantilever gate roller with double bearings and load rating of 3500 lbs.

This model fits standard 4 inch OD pipe mount and 2 1/2 inch OD pipe gate frames. Mounts available for 3, 3 1/2, 4, 4 1/2, and 6 5/8 inch OD Pipe




FS-8000 graphite impregnated nylon cantilever gate roller.

Load rating 2200 lbs. Mounts available for 3, 3 1/2, 4, 4 1/2, 6 5/8 inch OD Pipe



FS-3500. Graphite impregnated nylon cantilever gate roller. Fits 2 inch square tubing and is shown with four inch square mount. Available in mounts for 3, 4, and 6 inch square, 3 inch, 3 1/2 inch, 4 inch, 4 1/2 inch, and 6 5/8 inch OD pipe sizes. 2200 lb. Rating.



FS-5000 Graphite Impregnated Nylon cantilever gate roller.

Shown with 4 inch round OD pipe mount. Roller fits 1 7/8 inch OD pipe gate frames. 2200 lb. Rating. Mounts available for 3, 3 1/2, 4, 4 1/2, 6 5/8 OD pipe.



FS-1200T injection molded top roller safety cover.



FS-1200B injection molded Bottom roller safety cover.



FS-2000-BR roll gate track roller
fits 1 5/8 inch pipe tracks
350 lb. Rating
Injection Molded Dupont Delrin

We have available post mounts for 8 5/8 inch OD pipe.

Phone Toll Free (800) 261-5547 Fax Toll Free (888) 772-7618

15512 North Pinewood Way, Hayden Lake, Idaho 83835